



# MANUFACTURER NEWLIFE MAGNETICS

## SPECIFICATION SHEET

### RUBBER STEEL SHEETING WITH MATT WHITE VINYL

Edition: A0 NO: NMEQS-MACO 074

#### FEATURES AND ADVANTAGES:

- Matte white vinyl bonded to rubber steel sheeting, is compatible for Eco Solvent, UV curable and UV screen printing.
- Rubber Steel sheeting is attracted to magnets, easy to apply, remove and change, without leaving any residue.
- Infinite magnetic receptivity, material will not rust.




#### DRAWING:

- matte white vinyl: 4mil(100μm)
- Rubber steel sheeting: 20mil(500um)

#### PACKAGING:



3" core



lid-tray box

#### PROCESS AND STORAGE:

- Working condition: temperature 15°C/59°F to 30°C/86°F, and relative humidity 30% to 60%.
- Application condition: temperature change is within 40°C /104°F daily.
- Storage condition: avoid direct sunlight, storage temperature 10°C/50°F to 35°C/95°F, relative humidity 20% to 70%
- Shelf life: 12 months under normal storage conditions. Unfinished material should be re-sealed, and used within one month.

#### PRINTING INDEX:

- compatible
- Δ testing required
- × not compatible

(ECO) SOLVENT	UV CURABLE Soft UV ink	LATEX	DYE/PIGMENT	OFFSET/FLEXO	SCREEN PRINT	TONER BASED
○	○	×	×	○	○	×

#### SPECIFICATION DATA:

PART NO.	MAGNET THICKNESS (INCH/MM)	TOTAL THICKNESS (INCH/MM)	WEIGHT (G/M2)	MAGNETIC DATA LIFTING WEIGHT *
RS-MWC-024...	.020"/0.51mm	.024"/0.61mm	1940	≥22g/cm2

\* Condition: the standard test tool is isotropic rubber magnet 0.7mm (holding strength is about 40g/cm2), test equipment is Tensile Strength Tester.